



The "LEDGE"

Chassis & Reader Specs

- Size: 6" X 4.5" X 1"
- USB 3.0 connector: 1
- USB 2.0 connectors: 4
- RJ45 10/100/1000 Mbps Ethernet Connector*: 1
- PCIe x1 connector (optional)
- 12VDC 2.5mm center pin input power jack
- Mini-DisplayPort (HDMI capable) connector: 1
- Reset and system On-Off headers
- 4A DC-DC Converter (for 3.3V req. in MiniDP & PCIe x1)
- 5V & 12V fan headers
- Red 5V & 12V power LED indicator and header
- Green Card Detect LED indicator and header
- BioDigitalPC® 100-pin docking connector
- 4mm mounting holes: 3
- External 12V PCIe power header
- *VMWare compatible
- Headers are standard 0.1" pitch

Computer Specs (can be changed)

- Quad core (8v Cores) Intel i7 processor
- 32GB of DDR4 RAM
- Powered by 5VDC and consumed between 10W and 15W
- 4 USB 2.0 and 1 USB 3.0
- 2 PCIe x1 Gen 3
- DisplayPort++: servicing DP, HDMI, DVI and VGA
- Operating Temperature: TBD
- 1TB NVMe vPro Virtualization Support
Trusted Platform Module Version 2.0



Deployable Technologies
708 Duncan Pl SE
Leesburg, Va. 20175

